

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
25 September 2003 (25.09.2003)


PCT

(10) International Publication Number
WO 03/077775 A1

- (51) International Patent Classification⁷: **A61B 17/17** (74) Agent: **BELCHER, Simon, James**; Urquhart-Dykes & Lord, Tower House, Merrion Way, Leeds LS2 8PA (GB).
- (21) International Application Number: **PCT/GB03/01157**
- (22) International Filing Date: **17 March 2003 (17.03.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
0206131.5 **15 March 2002 (15.03.2002)** **GB**
- (71) Applicant (for all designated States except US): **DEPUY INTERNATIONAL LIMITED** [GB/GB]; St. Anthony's Road, Beeston, Leeds LS11 8DT (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **ASHBY, Alan** [GB/GB]; 19 Clifton Green, York YO30 6LN (GB). **RE-VIE, Ian** [GB/GB]; Tutt House, New Row, Boroughbridge YO51 9AX (GB).
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**
- Published:
— with international search report

[Continued on next page]

(54) Title: **A SURGICAL NAVIGATION TOOL**



(57) Abstract: A navigation tool for locating an axis on or in relation to which an orthopaedic surgery procedure is to be performed includes a column member having upper and lower parts. The lower part can be fastened to a bone. The upper and lower parts are connected to one another with the mating surfaces in contact with one another in such a way that the upper and lower parts can be rotated relative to one another about an axis which is perpendicular to the mating planes. The tool also includes a guide having an opening extending through it, which is fastened to the upper part of the column member so that it extends transversely relative to the upper part of the column member and can be moved relative to the upper part of the column member so as to change the distance between the opening and the point at which the guide is fastened to the upper part of the column member.



WO 03/077775 A1



— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

-1-

A SURGICAL NAVIGATION TOOL

This invention relates to a surgical navigation tool.

It can be necessary in surgical procedures to drill a hole in a bone. The drilled hole might be used to fasten an implanted component or an instrument to the bone. It can be important that the location and orientation of the drilled hole is accurately controlled, for example to avoid damage to surrounding tissue. It can also be important to ensure proper positioning (for example location and alignment) of the component or instrument that is to be attached to the bone.

It is known for example to attach implanted components to a patient's spinal column using screws which are inserted into holes drilled in the pedicle. Such components can be used for example to restrict or to prevent relative movement between vertebrae. The use of screws has advantages over other fixation techniques, for example using hooks, because of the greater control that is available over the location of the components, both during and immediately after the surgical procedure, and also in the longer term. However, accurate location of the hole in the pedicle is fundamentally important in order to avoid damage to CNS tissue.

It is common to plan a surgical procedure using images of the patient's tissue, for example a CT image. This can be used to identify the site for fixation of an implant or an instrument, including for example the location and orientation of holes that have to be drilled in a patient's bone. It is necessary then to move from the CT image data to locate the fixation site relative to the bone itself. In the case of fixation to a patient's spinal column, it is an established technique to test the location of a fixation site by forming a pilot hole in the pedicle (for example using a drill bit or a pedicle probe). The hole can then be probed to ensure that the pedicle wall has not been penetrated. However, accurate location of the hole relative to the patient's bone can require generation of image data, for example using X-ray or fluoroscopy techniques.

CONFIRMATION COPY

-2-

In one aspect, the present invention provides an instrument for locating an axis on or in relation to which an orthopaedic surgery procedure is to be performed, which comprises:

- a. a column member comprising upper and lower parts of which the lower part can be fastened to a bone, the upper part having a mating surface at its lower end which defines an upper part mating plane and the lower part having a mating surface at its upper end which defines a lower part mating plane, the upper and lower parts being connected to one another with the mating surfaces in contact with one another in such a way that the upper and lower parts can be rotated relative to one another about an axis which is perpendicular to the mating planes, the axis being non-parallel to the axes of the upper and lower parts of the column member,
- b. a guide having an opening extending through it, which is fastened to the upper part of the column member so that it extends transversely relative to the upper part of the column member and can be moved relative to the upper part of the column member so as to change the distance between the opening and the point at which the guide is fastened to the upper part of the column member.

The tool of the present invention has the advantage that it allows an axis to be located accurately relative to a patient's bone accurately and simply. The two parts of the column member provide a simple mechanism for determining the orientation of the axis, and the movement of the guide relative to the upper part of the column member allows selection of the distance of the axis from the column member.

Preferably, the guide comprises a plate which has at least first and second openings extending through it, the distance from the point at which the plate is fastened to the upper part of the column member to the first opening being greater than the distance from the point at which the plate is fastened to the upper part of the column member to the second opening. For example, the plate can have a plurality of openings extending through it, arranged on a helical line around the point at which the plate is fastened to the upper part of the column member. The distance from the said fastening point to the closest opening is preferably not more than about 15 mm, more preferably not more than about 10 mm.

-3-

Preferably, the distance from the said fastening point to the opening which is furthest from the fastening point is at least about 20 mm, more preferably at least about 25 mm, especially at least about 30 mm.

The plate can have the configuration such as would result from it being formed from a continuous sheet of material. However, the plate can have other configurations, for example comprising a plurality of spokes in which the openings are provided. The spokes can be formed from a continuous sheet of material. However, the plate can be formed from more than one piece of material: for example, when the plate comprises a plurality of spokes, the spokes can be provided by different pieces of material which are joined together to form the plate.

The guide component of the instrument can be an arm which has an opening in it. Preferably, the length of the arm can be varied, for example by means of two telescoping parts. The length of the arm can be controlled by means of a driver which moves the parts relative to one another, for example by means of a stepping motor.

Preferably, the guide can be rotated relative to the upper part of the column member, about the point at which the guide is fastened to the upper part of the column member. It is particularly preferred that the tool includes a motor for rotating the guide relative to the upper part of the column member.

Preferably, each of the mating surfaces of the upper and lower parts of the column member is planar. However, the surfaces might be non-planar, for example to make the engagement of the upper and lower parts of the column member more secure. For example, one of the mating surfaces might have a recess formed in it, and the other of the mating surfaces might have a protrusion which can fit into the recess. The mating planes that are defined by the surfaces will generally be defined by the edges of the surfaces, and will be perpendicular to the axis about which the parts rotate relative to one another.

Preferably, the angle between the axis of relative rotation and the axis of the upper part of the column member is the same as the angle between that rotation axis and the axis of the

-4-

lower part of the column member. Preferably, the angle between the axis of relative rotation and the axis of the lower part of the column member is at least about 5° , more preferably at least about 10° , for example about 15° .

Preferably, the height of the column member is at least about 25 mm, more preferably at least about 40 mm, especially at least about 60 mm.

Preferably, the instrument includes a motor for rotating upper part of the column member relative to the lower part of the column member.

Preferably, the instrument includes a connector by which the lower part of the column member can be fastened to a bone. For example, the connector can comprise clamp parts which are configured to fit on to bone structures. Alternatively, the connector can be fitted to wires which are fastened to bone structures, for example by insertion into the spinal process in the case of a spinal application. Suitable clamp parts are known, for fitting to a patient's spinal column or to another bone structure. The lower part of the column member can be attached to the connector, preferably so that rotation of the lower part of the column member relative to the bone, around the axis of the lower part of the column member, is permitted. Preferably, the instrument includes a motor for rotating the lower part of the column member relative to the bone.

Preferably, the instrument of the invention includes at least one marker by which the tool can be located relative to the patient's bone. Generally, the instrument will include a plurality of markers, for example two, three or four markers. These can be used to locate the instrument relative to anatomical landmarks on the patient's bone, or relative to markers which have been implanted in the patient's bone. The nature of the markers will depend on the nature of the monitoring system which is being used to locate the instrument. For example, the markers can be selected to be visible using fluoroscopic techniques, or the instrument can have a shadow which is uniquely identifiable in the fluoroscopic image.

Preferably, the guide component of the instrument is made from a radio-translucent material so that it does not prevent the creation of images of the patient's bone. Other

-5-

components of the instrument can also be made from radio-translucent material. However, it can be preferred for other components to be made from metals in some cases. Examples of suitable metals might include certain stainless steels and titanium-based alloys.

Preferably, one or more motors which are incorporated in the instrument are controlled using appropriate computer apparatus. For example, the motors might be stepping motors, controlled by appropriate pulse drive signals which are generated by a computer.

In another aspect, the invention provides a navigation system for locating an axis on or in relation to which an orthopaedic surgery procedure is to be performed, which comprises a navigation tool as discussed above. The system can include other components. For example, it can include a cutting tool which can be used to cut the bone along an axis that is determined by the navigation tool. The cutting tool can be a drill. The cutting tool can fit through the opening in the guide when appropriately aligned relative to a patient's bone, to drill a hole in the bone. Alternatively, a separate guide can be positioned using the navigation tool of the invention, which is then used to align a drill or other cutting tool.

The navigation system of the invention can include a computer which is used to control the navigation tool, for example to provide drive signals to motors by which components of the navigation tool are moved relative to one another. The navigation system can include sensors for determining the location of the navigation tool.

Embodiments of the present invention will now be described by way of example with reference to the accompanying drawings, in which:

Figure 1 is a side view of the navigation tool of the present invention.

Figure 2 is a plan view of the tool shown in Figure 1.

Figure 3 is an isometric view of a clamp which can be used to fasten the navigation tool to a patient's spinal column.

-6-

Figure 4 is a view of the navigation tool of the present invention positioned in relation to a patient's spinal column so as to enable the axis for a drilling step into the pedicle to be defined:

Referring to the drawings, Figure 1 shows a navigation tool 2 which comprises a column member having an upper part 4 and a lower part 6. The lower part 6 can be fastened to a clamp 8 which can be fitted to a patient's bone.

The tool 2 includes a guide plate 10.

The upper part 4 of the column member has a lower face which defines a mating plane 12, which is inclined to the axis 14 of the upper part at an angle of 15° . Similarly, the lower part 6 of the column member has an upper face which is inclined to the axis 18 of the lower part an angle of 15° . The lower face of the upper part and the upper face of the lower part are in face-to-face contact with one another on the mating plane.

The tool includes a guide plate 10 which is fastened to the upper part 4 of the column member at (or towards) its upper end. As shown in Figure 2, the guide plate has a series of openings 20 extending through it, arranged on the surface of the guide plate on a line 24 which follows a helical path around the centre of the plate.

The lower part 6 of the column member is able to rotate relative to the clamp 8. The guide plate 10 is able to rotate relative to the upper part 4 of the column member. The upper part 4 of the column member is able to rotate on the mating plane 12 relative to the lower part 6. Relative rotation between the upper and lower parts of the column member causes the angle between the axes 14, 18 to change, between 0° as shown in Figure 1 and 30° when the upper part has been rotated relative to the lower part through 180° . Motors are provided in the column member by which the relative rotation of adjacent parts of the navigation tool can be controlled. Signals for driving the motors in the column member can be generated using a computer having appropriate software. For example, when the motors are stepping motors, the control system can generate pulse signals to drive the motors.

-7-

Figure 3 shows a clamp 40 which is fastened to a patient's vertebra 42, and which provides a platform 44 on which the tool of the invention can be mounted. The precise form of the clamp is not important to the function of the tool. The clamp should provide a secure mounting platform which is located stably relative to the bone. Such clamps are known.

Figure 4 shows a vertebra 50 viewed along the spinal axis which has a navigation tool according to the present invention held in relation thereto in order to allow a drilling axis 52 to be identified so that a hole can be drilled into the patient's pedicle.

Use of the system of the present invention to define the axis for drilling into a patient's bone (for example the spinal pedicle) involves the following sequence of steps:

1. The location of a drill axis is determined in pre-operative planning using appropriate images of the patient's bone, so that the location of the axis is known relative to reference points on the patient's bone (which can be provided by implanted markers or by anatomical landmarks).
2. A small incision is made to allow access to the patient's bone.
3. The clamp for the navigation tool is fastened to the bone, for example by directly engaging the bone tissues, or by means of previously fixed wires.
4. The tool is positioned in a reference configuration.
5. The location and orientation of the tool is determined relative to implanted markers or anatomical landmarks on the patient's bone using appropriate inspection or scanning instrumentation. For example, a fluoroscopic imaging system could be used to generate two calibrated, stereoscopic, synchronized images to identify the location of the drill guide and the bone to which it is attached in 3 dimensional space. The trajectory of the drill can then be planned and the resultant axis and direction of the guide programmed from this plan. The orientation of the guide could then be positioned as described below.
6. Drive signals are supplied to the navigation tool of the invention, involving relative movement between (a) the upper and lower parts of the column member, (b) the lower part of the column member and the clamp, and (c) the upper part of the column member and the guide plate, so that one of the openings in the guide plate is positioned and

-7-

Figure 3 shows a clamp 40 which is fastened to a patient's vertebra 42, and which provides a platform 44 on which the tool of the invention can be mounted. The precise form of the clamp is not important to the function of the tool. The clamp should provide a secure mounting platform which is located stably relative to the bone. Such clamps are known.

Figure 4 shows a vertebra 50 viewed along the spinal axis which has a navigation tool according to the present invention held in relation thereto in order to allow a drilling axis 52 to be identified so that a hole can be drilled into the patient's pedicle.

Use of the system of the present invention to define the axis for drilling into a patient's bone (for example the spinal pedicle) involves the following sequence of steps:

1. The location of a drill axis is determined in pre-operative planning using appropriate images of the patient's bone, so that the location of the axis is known relative to reference points on the patient's bone (which can be provided by implanted markers or by anatomical landmarks).
2. A small incision is made to allow access to the patient's bone.
3. The clamp for the navigation tool is fastened to the bone, for example by directly engaging the bone tissues, or by means of previously fixed wires.
4. The tool is positioned in a reference configuration.
5. The location and orientation of the tool is determined relative to implanted markers or anatomical landmarks on the patient's bone using appropriate inspection or scanning instrumentation. For example, a fluoroscopic imaging system could be used to generate two calibrated, stereoscopic, synchronized images to identify the location of the drill guide and the bone to which it is attached in 3 dimensional space. The trajectory of the drill can then be planned and the resultant axis and direction of the guide programmed from this plan. The orientation of the guide could then be positioned as described below.
6. Drive signals are supplied to the navigation tool of the invention, involving relative movement between (a) the upper and lower parts of the column member, (b) the lower part of the column member and the clamp, and (c) the upper part of the column member and the guide plate, so that one of the openings in the guide plate is positioned and

-8-

oriented appropriately to define a drill axis extending into the patient's bone, consistent with that defined in the pre-operative planning.

7. A drill is used extending along the axis defined by the opening in the guide member to form a bore in the bone.



CLAIMS:

1. A navigation tool for locating an axis on or in relation to which an orthopaedic surgery procedure is to be performed, which comprises:
 - a. a column member comprising upper and lower parts of which the lower part can be fastened to a bone, the upper part having a mating surface at its lower end which defines an upper part mating plane and the lower part having a mating surface at its upper end which defines a lower part mating plane, the upper and lower parts being connected to one another with the mating surfaces in contact with one another in such a way that the upper and lower parts can be rotated relative to one another about an axis which is perpendicular to the mating planes, the axis being non-parallel to the axes of the upper and lower parts of the column member,
 - b. a guide having an opening extending through it, which is fastened to the upper part of the column member so that it extends transversely relative to the upper part of the column member and can be moved relative to the upper part of the column member so as to change the distance between the opening and the point at which the guide is fastened to the upper part of the column member.
2. A tool as claimed in claim 1, in which the guide comprises a plate which has at least first and second openings extending through it, the distance from the point at which the plate is fastened to the upper part of the column member to the first opening being greater than the distance from the point at which the plate is fastened to the upper part of the column member to the second opening.
3. A tool as claimed in claim 2, in which the plate has a plurality of openings extending through it, arranged on a helical line around the point at which the plate is fastened to the upper part of the column member.

-10-

4. A tool as claimed in claim 1, in which the guide can be rotated relative to the upper part of the column member, about the point at which the guide is fastened to the upper part of the column member.
5. A tool as claimed in claim 4, which includes a motor for rotating the guide relative to the upper part of the column member.
6. A tool as claimed in claim 1, which includes a motor for rotating upper part of the column member relative to the lower part of the column member.
7. A tool as claimed in claim 1, which includes a connector by which the lower part of the column member can be fastened to a bone.
8. A tool as claimed in claim 7, in which the connector permits rotation of the lower part of the column member relative to the bone, around the axis of the lower part of the column member.
9. A tool as claimed in claim 8, which includes a motor for rotating the lower part of the column member relative to the bone.
10. A tool as claimed in claim 1, which includes at least one marker by which the tool can be located relative to the patient's bone.
11. A navigation system for locating an axis on or in relation to which an orthopaedic surgery procedure is to be performed, which comprises a navigation tool as claimed in claim 1, and a cutting tool which can be used to cut the bone along an axis that is determined by the navigation tool.

-1/2-

FIG. 1FIG. 2

-2/2-

FIG. 3





FIG. 4

INTERNATIONAL SEARCH REPORT

 Intern: application No
 PCT/GB 03/01157

 A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 A61B17/17

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 891 516 A (BALTER VALENTIN) 2 January 1990 (1990-01-02) column 5, line 7 - line 16; figures 1,2 ---	1,11
A	US 5 569 247 A (MORRISON MATTHEW M) 29 October 1996 (1996-10-29) column 3, line 33 - line 45; figures 4,5 ---	1,11
A	DE 297 03 947 U (PLUS ENDOPROTHETIK AG) 5 June 1997 (1997-06-05) page 8, line 30 -page 10, line 4; figures 6-8 -----	1,11

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

7 August 2003

Date of mailing of the international search report

18/08/2003

Name and mailing address of the ISA

 European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Ducreau, F

INTERNATIONAL SEARCH REPORT

Internal application No
PCT/JP 03/01157

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4891516	A	02-01-1990	NONE	
US 5569247	A	29-10-1996	NONE	
DE 29703947	U	05-06-1997	DE 29703947 U1 CH 692023 A5	05-06-1997 15-01-2002